



# SAFETY DATA SHEET

according to NOHSC:1015(2001) and NOHSC:2011(2003)

## 5W-30 MOPAR ENGINE OIL, synthetic

Material number 68231015

Revision date: 30/6/2014

Version: 1

Language: en-AU

Date of print: 19/8/2014

Page: 1 of 7

Not classified as hazardous according to criteria of NOHSC.

### 1. Identification of the substance/mixture and of the company/undertaking

#### Product identifier

Trade name: 5W-30 MOPAR ENGINE OIL, synthetic  
This safety data sheet pertains to the following products:  
68231014GA  
68231015GA

#### Relevant identified uses of the substance or mixture and uses advised against

General use: Engine oil.

#### Details of the supplier of the safety data sheet

Company name: Chrysler Australia Pty Ltd.  
Street/POB-No.: 437 Plummer Street, Port Melbourne  
Postal Code, city: AUS-3207 Melbourne  
Dept. responsible for information:  
After-Sales  
Telephone: +86 21 6192 7899  
E-mail: SDS@Chrysler.com

#### Emergency telephone number

Telephone: 0459 988 123 / +61 (0)3 8698 0255

### 2. Hazards identification

#### Other hazards

Avoid breathing mist/vapours. Inhaling can lead to irritations of the respiratory tract and mucous membrane. Frequent or prolonged skin contact may cause irritation and inflammation. Injection of oil into the skin may cause permanent local skin damage. There may be no signs of initial injury or pain. Prolonged/repetitive skin contact may cause skin defatting or dermatitis. Upon direct contact with eyes may cause burning, tearing, redness. Special danger of slipping by leaking/spilling product.

### 3. Composition / information on ingredients

#### Mixtures

Chemical characterization:

Engine oil of the following listed substances with safe additions.

Hazardous ingredients:

CAS No.	Designation	Content	Classification
CAS 125643-61-0	Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, C7-9-branched alkyl esters	1 - 3 %	Aquatic toxicity - chronic - Category 4.

Additional information: Contains: Oil, < 3% dimethylsulfoxide (DMSO) extract, according to IP 346.



# SAFETY DATA SHEET

according to NOHSC:1015(2001) and NOHSC:2011(2003)

## 5W-30 MOPAR ENGINE OIL, synthetic

Material number 68231015

Revision date: 30/6/2014

Version: 1

Language: en-AU

Date of print: 19/8/2014

Page: 2 of 7

### 4. First aid measures

- In case of inhalation: Move victim to fresh air, provide oxygen as needed. In case of irregular breathing or respiratory arrest provide artificial respiration. Seek medical treatment in case of troubles.
- In case of skin contact: After contact with skin, wash immediately with soap and plenty of water. Then cream your skin. Change contaminated clothing. In case of skin irritation, consult a physician. Injection of oil into the skin may cause permanent local skin damage. Immediately get medical attention.
- After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. In case of troubles or persistent symptoms, consult an ophthalmologist.
- After swallowing: Never give anything by mouth to an unconscious person. Rinse mouth. Do not induce vomiting. In case of vomiting, lay at least head on side. Seek medical treatment in case of troubles.

#### Most important symptoms and effects, both acute and delayed

- In case of inhalation:  
Overheating released spray or vapours can irritate the respiratory tracts.  
Other symptoms: Cough, respiratory complaints, dizziness, nausea.
- In case of ingestion:  
Following symptoms can occur depending on degree of seriousness: Nausea, gastrointestinal complaints, vomiting, diarrhoea.
- After contact with skin:  
Frequent or prolonged skin contact may cause irritation and inflammation.  
Prolonged/repetitive skin contact may cause skin defatting or dermatitis.  
Other symptoms: skin rash, irritation.  
Injection of oil into the skin may cause permanent local skin damage. There may be no signs of initial injury or pain.
- After eye contact:  
Product can cause slight irritation. Upon direct contact with eyes may cause burning, tearing, redness.

#### Indication of any immediate medical attention and special treatment needed

- Treat symptomatically.

### 5. Firefighting measures

#### Extinguishing media

- Suitable extinguishing media:  
Foam, water fog, extinguishing powder, carbon dioxide, sand.
- Extinguishing media which must not be used for safety reasons:  
Full water jet

#### Special hazards arising from the substance or mixture

- This material is combustible, but will not ignite readily. The product may release harmful vapours by heating. Vapours can form explosive mixtures with air.  
In case of fire may be liberated: Toxic gases/vapours, hydrocarbons, carbon monoxide and carbon dioxide.

#### Advice for firefighters

- Special protective equipment for firefighters:  
Treat as oil fire. Wear a self-contained breathing apparatus and chemical protective clothing.



# SAFETY DATA SHEET

according to NOHSC:1015(2001) and NOHSC:2011(2003)

## 5W-30 MOPAR ENGINE OIL, synthetic

Material number 68231015

Revision date: 30/6/2014

Version: 1

Language: en-AU

Date of print: 19/8/2014

Page: 3 of 7

Additional information: Hazchem-Code: -  
Heating causes rise in pressure with risk of bursting. Cool endangered containers with water spray and, if possible, remove from danger zone. Use water spray jet to knock down vapours. Do not breathe fumes. Do not allow fire water to penetrate into surface or ground water.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so. Avoid contact with the substance. Avoid formation of aerosols/vapours. Do not breathe vapour/aerosol. If vapours form, use respiratory protection. Ensure adequate ventilation, especially in confined areas.

### Environmental precautions

Do not allow to penetrate into soil, waterbodies or drains. If necessary notify appropriate authorities.

### Methods and material for containment and cleaning up

Plug leak if safely possible. Collect with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents, or sawdust) and place in closed containers for disposal. Final cleaning. Dispose of waste according to applicable legislation.

Additional information: Special danger of slipping by leaking/spilling product.

## 7. Handling and storage

### Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Avoid prolonged, intensive skin contact and contact with the eyes. Avoid formation of aerosols/vapours. Do not breathe vapour/aerosol. If vapours form, use respiratory protection. Don't put cleaning rags fouled by oil into trousers pockets. When using do not eat, drink or smoke.

Precautions against fire and explosion:

Usual measures for fire prevention. Keep away from heat sources, sparks and open flames. Use only non-sparking tools. Take precautionary measures against static discharges. Ensure that the equipment is adequately grounded.

### Storage

Requirements for storerooms and containers:

Keep container tightly closed in a cool, well-ventilated place. Store in a dry place. Do not drop, drag or bang the container. Store at room temperature.

Protect from frost. Keep away from incompatible materials.

Suitable material for containers/equipment: Polyethylene.

Unsuitable container/equipment material: PVC.

Hints on joint storage: Do not store together with strong oxidizing agents.  
Keep away from food, drink and animal feedingstuffs.

## 8. Exposure controls/personal protection

### Control parameters

Occupational exposure limit values:

Type	Limit value
Australia: OEL-TWA	5 mg/m <sup>3</sup> Oil fog



# SAFETY DATA SHEET

according to NOHSC:1015(2001) and NOHSC:2011(2003)

## 5W-30 MOPAR ENGINE OIL, synthetic

Material number 68231015

Revision date: 30/6/2014

Version: 1

Language: en-AU

Date of print: 19/8/2014

Page: 4 of 7

### Exposure controls

Provide for good room ventilation, suctioning/venting.  
See also information in chapter 7, section storage.

### Personal protection equipment

#### Occupational exposure controls

- Respiratory protection: If vapours form, use respiratory protection.  
Use filter type A (= against vapours of organic substances) according to AS/NZS 1716.  
Have a breathing apparatus that is not dependent on the circulating air ready for emergencies.
- Hand protection: Recommended:  
Protective gloves according to AS/NZS 2161.  
Glove material: Neoprene (0.35 mm), nitrile rubber (0.35 mm)  
Breakthrough time: >480 min.  
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
- Eye protection: Tightly sealed eye protectors according to AS/NZS 1337.
- Body protection: Recommended: Wear suitable protective clothing.
- General protection and hygiene measures:  
Avoid prolonged, intensive skin contact and contact with the eyes. Change contaminated clothing. Avoid formation of aerosols/vapours. Do not breathe vapour/aerosol. Have eye wash bottle or eye rinse ready at work place. After work, wash hands and face.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

- Appearance: Physical state: liquid  
Colour: amber
- Odour: weak, hydrocarbons
- Odour threshold: no data available
- pH value: not applicable
- Melting point/freezing point: no data available
- Initial boiling point and boiling range: > 280 °C
- Flash point/flash point range: 248 °C (coc)
- Evaporation rate: no data available
- Flammability: This material is combustible, but will not ignite readily.
- Explosive properties: In case of heating: Vapours can form explosive mixtures with air.
- Explosion limits: LEL (Lower Explosion Limit): 1.00 Vol-%  
UEL (Upper Explosion Limit): 10.00 Vol-%
- Vapour pressure: at 20 °C: <= 0.5 Pa
- Vapour density: >= 1
- Density: at 15 °C: 0.848 g/mL
- Water solubility: negligible
- Partition coefficient: n-octanol/water: >= 6
- Auto-ignition temperature: > 320 °C
- Thermal decomposition: no data available

### Additional information

- Viscosity, kinematic: at 40 °C: 74 mm<sup>2</sup>/s
- Additional information: Pour point: -48 °C



## SAFETY DATA SHEET

according to NOHSC:1015(2001) and NOHSC:2011(2003)

### 5W-30 MOPAR ENGINE OIL, synthetic

Material number 68231015

Revision date: 30/6/2014

Version: 1

Language: en-AU

Date of print: 19/8/2014

Page: 5 of 7

## 10. Stability and reactivity

- Reactivity: Refer to section: Possibility of hazardous reactions.
- Chemical stability: Stable under recommended storage conditions.
- Possibility of hazardous reactions:  
The product may release harmful vapours by heating. Vapours can form explosive mixtures with air.  
Hazardous polymerisation: will not occur.  
No dangerous reactions with proper and specified storage and handling.
- Conditions to avoid: Excessive heating. Keep away from sources of ignition. Avoid formation of aerosols/vapours.
- Incompatible materials: Strong oxidizing agents.
- Hazardous decomposition products:  
In case of fire may be liberated: Toxic gases/vapours, hydrocarbons, carbon monoxide and carbon dioxide.
- Thermal decomposition: no data available

## 11. Toxicological information

### Information on toxicological effects

- Toxicological effects: Acute toxicity (oral): Based on available data, the classification criteria are not met.  
Acute toxicity (dermal): Based on available data, the classification criteria are not met.  
Acute toxicity (inhalative): Lack of data.  
Skin corrosion/irritation: Lack of data.  
Eye damage/irritation: Lack of data.  
Sensitisation to the respiratory tract: Lack of data.  
Skin sensitisation: Lack of data.  
Germ cell mutagenicity/Genotoxicity: Lack of data.  
Carcinogenicity: Lack of data.  
Reproductive toxicity: Lack of data.  
Effects on or via lactation: Lack of data.  
Specific target organ toxicity (single exposure): Lack of data.  
Specific target organ toxicity (repeated exposure): Lack of data.  
Aspiration hazard: Lack of data.
- Other information: The statement is derived from the properties of the single components. The statement is derived from products of similar structure or composition.  
LD50, Rat (oral): > 5000 mg/kg  
LD50, Rabbit (dermal): > 5000 mg/kg  
Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.  
Used oil: Evidence for possible carcinogenic effects in experimental animals existent.



# SAFETY DATA SHEET

according to NOHSC:1015(2001) and NOHSC:2011(2003)

## 5W-30 MOPAR ENGINE OIL, synthetic

Material number 68231015

Revision date: 30/6/2014

Version: 1

Language: en-AU

Date of print: 19/8/2014

Page: 6 of 7

### Symptoms

In case of inhalation:

Overheating released spray or vapours can irritate the respiratory tracts.

Other symptoms: Cough, respiratory complaints, dizziness, nausea.

In case of ingestion:

Following symptoms can occur depending on degree of seriousness: Nausea, gastrointestinal complaints, vomiting, diarrhoea.

After contact with skin:

Frequent or prolonged skin contact may cause irritation and inflammation.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Other symptoms: skin rash, irritation.

Injection of oil into the skin may cause permanent local skin damage. There may be no signs of initial injury or pain.

After eye contact:

Product can cause slight irritation. Upon direct contact with eyes may cause burning, tearing, redness.

## 12. Ecological information

### Toxicity

Aquatic toxicity:

The statement is derived from the properties of the single components. The statement is derived from products of similar structure or composition.

LL50/EL50/IL50 (aquatic organisms): > 100 mg/L

### Persistence and degradability

Further details:

Product is not readily biodegradable.

### Mobility in soil

Floats on the water.

Mobility in soil: None.

### Additional ecological information

General information:

Do not allow to enter into ground-water, surface water or drains.

## 13. Disposal considerations

### Waste treatment methods

#### Product

Recommendation:

Dispose of waste according to applicable legislation.

#### Contaminated packaging

Recommendation:

Dispose of waste according to applicable legislation. Do not remove label until container is thoroughly cleaned. Non-contaminated packages may be recycled.

## 14. Transport information

### Land transport (ADR/RID)

Product designation:

Not restricted



## SAFETY DATA SHEET

according to NOHSC:1015(2001) and NOHSC:2011(2003)

### 5W-30 MOPAR ENGINE OIL, synthetic

Material number 68231015

Revision date: 30/6/2014

Version: 1

Language: en-AU

Date of print: 19/8/2014

Page: 7 of 7

#### Sea transport (IMDG)

Proper shipping name: Not restricted

Marine pollutant: No

#### Air transport (IATA)

Proper shipping name: Not restricted

#### Further information

No dangerous good in sense of these transport regulations.

## 15. Regulatory information

#### National regulations - Australia

Hazchem-Code: -

## 16. Other information

Date of first version: 30/6/2014

#### Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.